

Section: [Ordination analysis](#)

Forward selection (constrained ordination)

Theory R functions **Examples** Exercise 

Example 1: tb-RDA with forward selection: Which chemical variables measured in fen water are important for vegetation of Carpathian wetlands?

First, prepare the [data](#):

```
# Carpathian wetlands - import data
vasc <- read.delim
('https://raw.githubusercontent.com/zdealveindy/anadat-r/master/data/vasc_pl
ants.txt', row.names = 1)
chem <- read.delim
('https://raw.githubusercontent.com/zdealveindy/anadat-r/master/data/chemist
ry.txt', row.names = 1)

# transform data using Hellinger transformation to prepare them for tb-RDA:
library (vegan)
vasc.hell <- decostand (vasc, 'hell')

# the last variable in the 'chem' dataset is 'slope', which is not a
chemical variable - remove it:
chem1 <- chem[, -15]
```

Then, test the global model (including all explanatory variables from which you plan to do selection) to see whether it is significant; if it is not, the forward selection should not be done.

```
tb_rda.all <- rda (vasc.hell ~ ., chem1)
anova (tb_rda.all) # 0.001 *** - it is significant
RsquareAdj (tb_rda.all)$adj.r.squared # 0.2011048 - adjusted R2 explained by
all 14 variables is 20.1%
```

Option a) Use of forward.sel function

The function `forward.sel` from the package `adespatial` is elaborated forward selection approach based on linear constrained ordination (i.e. based on RDA - if you want to calculate CCA, you cannot use this function and need to resolve to use `ordiR2step` from `vegan` instead). Along to the testing significance of selected variable, this function includes also other stopping rules, published by [Blanchet et al. \(2008\)](#). The method based on significance is prone to be inflated, which may result into models with too many variables; [Blanchet et al. \(2008\)](#) came with another stopping rules along to the significance one. First, adjusted R^2 of the model including all variables (from which the selection is made) is calculated. While selecting variables during the selection process, the selection stops if (1) the next selected variables is not significant (does not significantly improve the explained variation), and (2) if the R^2_{adj} of the model including this variable exceeds the R^2_{adj} of the global model.

```
# install.packages ('adespatial') # run this code if you haven't install  
the adespatial package before  
library (adespatial)  
sel.fs <- forward.sel (vasc.hell, chem1) # forward.sel calculates only RDA  
(or tb-RDA in case of Hell. transformed data)
```

```
Testing variable 1  
Testing variable 2  
Testing variable 3  
Testing variable 4  
Testing variable 5  
Testing variable 6  
Testing variable 7  
Testing variable 8  
Procedure stopped (alpha criteria): pvalue for variable 8 is 0.118000 (>  
0.050000)
```

See the table with selected variables saved in sel.fs object:

```
sel.fs
```

	variables	order	R2	R2Cum	AdjR2Cum	F	pval
1	Ca	1	0.13898260	0.1389826	0.1263206	10.976337	0.001
2	conduct	14	0.03248342	0.1714660	0.1467337	2.626796	0.001
3	Si	6	0.02722659	0.1986926	0.1622696	2.242529	0.001
4	NH3	10	0.02398868	0.2226813	0.1748463	2.005953	0.002
5	N03	9	0.02112004	0.2438013	0.1847233	1.787470	0.001
6	Mg	2	0.01914995	0.2629513	0.1927562	1.636862	0.003
7	pH	13	0.01744989	0.2804012	0.1991562	1.503467	0.024

Or, if you want to see only the names of selected variables, subset it from the sel.fs object:

```
sel.fs$variables
```

```
[1] "Ca" "conduct" "Si" "NH3" "N03" "Mg" "pH"
```

Since there is (a potentially high) number of tests of significance during the forward selection procedure, it is better to apply a correction for multiple testing issue. The most common correction (but rather conservative) is Bonferroni, which multiplies each calculated P -value by the overall number of tests. In the forward selection, the overall number of tests (which can be potentially done) equals to the number of variables from which the selection is made (i.e. not the number of selected variables), and this should be considered while applying the adjustment.

The function available for adjusting the P -values is `p.adjust`. It can be applied on a single P -value or a vector of P -values, and optionally accepts also the argument `n` indicating the number of tests.

The P -values from the forward selection above are in the object `sel.fs$pval`, and the adjustment can be done in the following way (Holm's correction):

```
n.tests <- ncol (chem1) # number of tests equals to number of all variables
```

from which is being selected

```
pval.adj <- p.adjust (sel.fs$pval, method = 'holm', n = n.tests)
sel.fs$pval.adj <- pval.adj
sel.fs
```

	variables	order	R2	R2Cum	AdjR2Cum	F	pval	pval.adj
1	Ca	1	0.13898260	0.1389826	0.1263206	10.976337	0.001	0.014
2	conduct	14	0.03248342	0.1714660	0.1467337	2.626796	0.001	0.014
3	Si	6	0.02722659	0.1986926	0.1622696	2.242529	0.001	0.014
4	NH3	10	0.02398868	0.2226813	0.1748463	2.005953	0.003	0.033
5	N03	9	0.02112004	0.2438013	0.1847233	1.787470	0.005	0.050
6	Mg	2	0.01914995	0.2629513	0.1927562	1.636862	0.014	0.126
7	pH	13	0.01744989	0.2804012	0.1991562	1.503467	0.020	0.160

After the correction, the last two variables (Mg and pH) are already not significant.

It is possible to help the interpretation by adding the significance stars (e.g. three stars for $P < 0.001$). This can be done by many ways; perhaps the simplest is to use the function `stars.pval` from the package `gtools` (you need to install it if you haven't used it before):

```
# install.packages ('gtools')
sel.fs$pval.adj.stars <- gtools::stars.pval (pval.adj)
sel.fs
```

	variables	order	R2	R2Cum	AdjR2Cum	F	pval	pval.adj
	pval.adj.stars							
1	Ca	1	0.13898260	0.1389826	0.1263206	10.976337	0.001	0.014
*								
2	conduct	14	0.03248342	0.1714660	0.1467337	2.626796	0.001	0.014
*								
3	Si	6	0.02722659	0.1986926	0.1622696	2.242529	0.001	0.014
*								
4	NH3	10	0.02398868	0.2226813	0.1748463	2.005953	0.003	0.033
*								
5	N03	9	0.02112004	0.2438013	0.1847233	1.787470	0.005	0.050
*								
6	Mg	2	0.01914995	0.2629513	0.1927562	1.636862	0.014	0.126
7	pH	13	0.01744989	0.2804012	0.1991562	1.503467	0.020	0.160

Here, even the first selected variable has the significance $P < 0.05$ (one star). The reason is the number of permutations used in the `forward.sel` function, which by default equals to 999 (argument `nperm`). The lowest P -value which can be obtained with 999 permutations is $1/(999+1) = 0.001$, and the correction will considerably increase this value (to 0.014 in case of 14 variables). The workaround is to increase the number of permutations to be able to get lower P -values, which even after correction could still fall below 0.001 threshold (here using 49,999 permutations to achieve P -value $1/50000 = 0.00002$).

```
sel.fs <- forward.sel (vasc.hell, chem1, nperm = 49999)
pval.adj <- p.adjust (sel.fs$pval, method = 'holm', n = ncol (chem1))
sel.fs$pval.adj <- pval.adj
sel.fs$pval.adj.stars <- gtools::stars.pval (pval.adj)
```

sel.fs

	variables	order	R2	R2Cum	AdjR2Cum	F	pval	pval.adj	
	pval.adj.stars								
1	Ca	1	0.13898260	0.1389826	0.1263206	10.976337	0.00002	0.00028	

2	conduct	14	0.03248342	0.1714660	0.1467337	2.626796	0.00004	0.00052	

3	Si	6	0.02722659	0.1986926	0.1622696	2.242529	0.00016	0.00192	
	**								
4	NH3	10	0.02398868	0.2226813	0.1748463	2.005953	0.00080	0.00880	
	**								
5	N03	9	0.02112004	0.2438013	0.1847233	1.787470	0.00304	0.03040	
	*								
6	Mg	2	0.01914995	0.2629513	0.1927562	1.636862	0.00824	0.07416	
	.								
7	pH	13	0.01744989	0.2804012	0.1991562	1.503467	0.02094	0.16752	

Since the `forward.sel` function is not optimised, the calculation with 49,999 permutation take some time, but the reward is the *P*-values (after correction) below 0.001 in case of the first two variables.

You can see that `forward.sel` function selected (after the correction) five environmental variables, which together explain 18.5% of the variance (adjusted R2, the column `AdjR2Cum` in the table above showing cumulative adjusted R2 of all variables). This is just slightly less than 20.1% which is explained by global model with 14 variables (see the result of `RsquareAdj(rda.all)$adj.r.squared` above).

In this case, the results of `forward.sel` function are the same as `ordiR2step` and `ordistep` functions below (option b and c), with seven included environmental variables (if calculated without correction for multiple testing).

Option b) Use of `ordiR2step` function

The `vegan`'s function `ordiR2step` does similar job as `forward.sel` from `adespatial`, but it's use is a bit more complex. On the other side, the method is more general - it allows to use also CCA or db-RDA methods, while `forward.sel` is based purely on linear constrained ordination (RDA, and tb-RDA in the case that the species composition data are pre-transformed e.g. by Hellinger transformation). In the default setting the criteria for including the variable is based on both significance of the newly selected variables, and the comparison of adjusted variation (R^2_{adj}) explained by the selected variables to R^2_{adj} explained by the global model (with all variables); if the new variable is not significant *or* the R^2_{adj} of the model including this new variable would exceed the R^2_{adj} of the global model, the selection will be stopped.

To use the `ordiR2step` function, you need to specify two models - the "empty" model containing only intercept, and the "full" model including all variables (aka global model). Also, the argument `direction` allows for selecting the selection direction (`forward`, `backward`, `both`, with the default to `both`):

```
tb_rda.vasc.0 <- rda (vasc.hell ~ 1, data = chem1) # model containing only
```

```
species matrix and intercept
tb_rda.vasc.all <- rda (vasc.hell ~ ., data = chem1) # model including all
variables from matrix chem1 (the dot after tilde (~) means "include all from
data")
```

The function `ordiR2step` then uses the empty model and the scope (variables) from the full model to proceed the selection. Set `direction = 'forward'` to ensure that forward instead of stepwise selection is done, and increase the number of permutations to 999 (instead of default 499) to make results comparable to `forward.sel` (which by default is based on 999 permutations):

```
sel.osR2 <- ordiR2step (tb_rda.vasc.0, scope = formula (tb_rda.vasc.all),
direction = 'forward', permutations = 999)
```

Step: R2.adj= 0

Call: `vasc.hell ~ 1`

	R2.adjusted
<All variables>	0.201104784
+ Ca	0.126320581
+ conduct	0.109418731
+ Mg	0.106926067
+ Corg	0.076260217
+ pH	0.074169805
+ Na	0.043030978
+ NH3	0.031875777
+ Si	0.022863900
+ S04	0.018929801
+ K	0.015918981
+ N03	0.008112568
+ Fe	0.004863012
+ P04	0.002933349
<none>	0.000000000
+ Cl	-0.002347612

	Df	AIC	F	Pr(>F)
+ Ca	1	-47.149	10.976	0.001 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: R2.adj= 0.1263206

Call: `vasc.hell ~ Ca`

	R2.adjusted
<All variables>	0.2011048
+ conduct	0.1467337
+ NH3	0.1417066
+ Na	0.1403837
+ Si	0.1403827
+ pH	0.1403289
+ Mg	0.1386000

```
+ Corg      0.1375824
+ N03      0.1340217
+ K        0.1302515
+ Fe       0.1299960
+ S04      0.1266017
<none>    0.1263206
+ Cl       0.1254155
+ P04      0.1235944
```

```
          Df      AIC      F Pr(>F)
+ conduct  1 -47.841  2.6268  0.001 ***
```

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: R2.adj= 0.1467337

Call: vasc.hell ~ Ca + conduct

```
          R2.adjusted
<All variables>  0.2011048
+ Si             0.1622696
+ NH3           0.1592776
+ N03           0.1572584
+ Mg            0.1565375
+ Corg          0.1538422
+ Na            0.1533884
+ Fe            0.1517167
+ pH            0.1513672
+ K             0.1511453
+ S04           0.1495485
+ Cl            0.1470011
<none>          0.1467337
+ P04           0.1444723
```

```
          Df      AIC      F Pr(>F)
+ Si   1 -48.18  2.2425  0.002 **
```

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: R2.adj= 0.1622696

Call: vasc.hell ~ Ca + conduct + Si

```
          R2.adjusted
<All variables>  0.2011048
+ NH3           0.1748463
+ N03           0.1739710
+ Mg            0.1708815
+ Corg          0.1689184
+ pH            0.1667252
+ S04           0.1666206
+ Na            0.1661906
```

```

+ Fe          0.1655162
+ K           0.1653789
<none>       0.1622696
+ Cl         0.1620351
+ P04        0.1599773

```

```

      Df      AIC      F Pr(>F)
+ NH3  1 -48.308 2.006  0.001 ***
---
```

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: R2.adj= 0.1748463

Call: vasc.hell ~ Ca + conduct + Si + NH3

```

                R2.adjusted
<All variables> 0.2011048
+ N03           0.1847233
+ Mg            0.1835775
+ S04           0.1799079
+ pH            0.1798906
+ Corg          0.1793391
+ Fe            0.1786200
+ K             0.1766585
+ Na            0.1756240
<none>         0.1748463
+ Cl            0.1737180
+ P04           0.1725072

```

```

      Df      AIC      F Pr(>F)
+ N03  1 -48.236 1.7875  0.005 **
---
```

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: R2.adj= 0.1847233

Call: vasc.hell ~ Ca + conduct + Si + NH3 + N03

```

                R2.adjusted
<All variables> 0.2011048
+ Mg            0.1927562
+ pH            0.1907475
+ Corg          0.1890699
+ S04           0.1876281
+ Fe            0.1869468
+ K             0.1868746
+ Na            0.1848251
<none>         0.1847233
+ Cl            0.1834910
+ P04           0.1826904

```

```

      Df      AIC      F Pr(>F)
+ Mg  1 -48.032 1.6369  0.011 *

```

```
---  
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Step: R2.adj= 0.1927562

Call: vasc.hell ~ Ca + conduct + Si + NH3 + N03 + Mg

	R2.adjusted
<All variables>	0.2011048
+ pH	0.1991562
+ Corg	0.1963215
+ S04	0.1958876
+ K	0.1956246
+ Fe	0.1953612
<none>	0.1927562
+ Na	0.1922729
+ Cl	0.1915194
+ P04	0.1907648

	Df	AIC	F	Pr(>F)
+ pH	1	-47.709	1.5035	0.028 *

```
---  
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Step: R2.adj= 0.1991562

Call: vasc.hell ~ Ca + conduct + Si + NH3 + N03 + Mg + pH

	R2.adjusted
+ Corg	0.2023822
+ Fe	0.2015249
+ K	0.2014550
+ S04	0.2012822
<All variables>	0.2011048
<none>	0.1991562
+ Na	0.1988753
+ P04	0.1974424
+ Cl	0.1974018

sel.osR2

Call: rda(formula = vasc.hell ~ Ca + conduct + Si + NH3 + N03 + Mg + pH,
data = chem1)

	Inertia	Proportion	Rank
Total	0.5674	1.0000	
Constrained	0.1591	0.2804	7
Unconstrained	0.4083	0.7196	62

Inertia is variance

Eigenvalues for constrained axes:

RDA1	RDA2	RDA3	RDA4	RDA5	RDA6	RDA7
------	------	------	------	------	------	------


```
0.09590 0.01904 0.01205 0.01027 0.00871 0.00718 0.00595
```

Eigenvalues for unconstrained axes:

```
  PC1      PC2      PC3      PC4      PC5      PC6      PC7      PC8
0.03601 0.03279 0.02383 0.01908 0.01687 0.01593 0.01504 0.01358
(Showned only 8 of all 62 unconstrained eigenvalues)
```

The summary table is part of the `ordiR2step` function output, stored in the component `$anova`:

```
sel.osR2$anova
```

	R2.adj	Df	AIC	F	Pr(>F)	
+ Ca	0.12632	1	-47.149	10.9763	0.001	***
+ conduct	0.14673	1	-47.841	2.6268	0.001	***
+ Si	0.16227	1	-48.180	2.2425	0.002	**
+ NH3	0.17485	1	-48.308	2.0060	0.001	***
+ NO3	0.18472	1	-48.236	1.7875	0.005	**
+ Mg	0.19276	1	-48.032	1.6369	0.011	*
+ pH	0.19916	1	-47.709	1.5035	0.028	*
<All variables>	0.20111					

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1						

The result is exactly the same as results of `forward.sel` function and also as results of `ordistep` method based on P-values and AIC criteria (below). P-values can be adjusted for multiple testing (e.g. by Holm's correction) as follows:

```
sel.osR2_adj <- sel.osR2
sel.osR2_adj$anova$`Pr(>F)` <- p.adjust (sel.osR2$anova$`Pr(>F)` , method =
'holm', n = ncol (chem1))
sel.osR2_adj$anova
```

	R2.adj	Df	AIC	F	Pr(>F)	
+ Ca	0.12632	1	-47.149	10.9763	0.014	*
+ conduct	0.14673	1	-47.841	2.6268	0.014	*
+ Si	0.16227	1	-48.180	2.2425	0.022	*
+ NH3	0.17485	1	-48.308	2.0060	0.014	*
+ NO3	0.18472	1	-48.236	1.7875	0.050	*
+ Mg	0.19276	1	-48.032	1.6369	0.099	.
+ pH	0.19916	1	-47.709	1.5035	0.224	
<All variables>	0.20111					

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1						

You may consider to increase the number of permutations (argument `permutations` in `ordiR2step` to reach lower P-values; in the `forward.sel` example above we increased the permutations to 49,999 to make sure that even after adjustment of P-values the most significant one could be smaller than 0.001.

Option c) Use of ordistep function

Function `ordistep` performs step-wise selection of environmental variables based two criteria: if their inclusion into the model leads to significant increase of explained variance (the same as in `forward.sel` and `ordiR2step`), and if the AIC of the new model is lower than AIC of the more simple model. In contrary to previous functions, the function does not consider as criteria whether the adjusted R^2 of the model exceeds the adjusted R^2 of the global model. The use of `ordistep` function has the same logic as `ordiR2step`.

```
rda.vasc.0 <- rda (vasc.hell ~ 1, data = chem1) # model containing only  
species matrix and intercept  
rda.vasc.all <- rda (vasc.hell ~ ., data = chem1) # model including all  
variables from matrix chem1 (the dot after tilda (~) means ALL!)  
sel.os <- ordistep (rda.vasc.0, scope = formula (rda.vasc.all), direction =  
'forward')
```

Start: vasc.hell ~ 1

	Df	AIC	F	Pr(>F)	
+ Ca	1	-47.149	10.9763	0.005	**
+ conduct	1	-45.808	9.4775	0.005	**
+ Mg	1	-45.612	9.2612	0.005	**
+ Corg	1	-43.249	6.6964	0.005	**
+ pH	1	-43.091	6.5277	0.005	**
+ Na	1	-40.775	4.1026	0.005	**
+ NH3	1	-39.964	3.2718	0.005	**
+ Si	1	-39.316	2.6145	0.005	**
+ S04	1	-39.034	2.3314	0.005	**
+ K	1	-38.820	2.1162	0.010	**
+ N03	1	-38.267	1.5643	0.060	.
+ Fe	1	-38.038	1.3372	0.105	
+ P04	1	-37.902	1.2030	0.150	
+ Cl	1	-37.532	0.8384	0.700	

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: vasc.hell ~ Ca

	Df	AIC	F	Pr(>F)	
+ conduct	1	-47.841	2.6268	0.005	**
+ NH3	1	-47.430	2.2190	0.005	**
+ pH	1	-47.318	2.1081	0.005	**
+ Na	1	-47.322	2.1125	0.010	**
+ Si	1	-47.322	2.1124	0.010	**
+ Mg	1	-47.177	1.9694	0.010	**
+ Corg	1	-47.095	1.8880	0.010	**
+ N03	1	-46.806	1.6047	0.035	*
+ K	1	-46.502	1.3073	0.110	
+ Fe	1	-46.482	1.2873	0.115	
+ S04	1	-46.209	1.0219	0.435	

```
+ Cl      1 -46.114 0.9296 0.590
+ P04     1 -45.968 0.7885 0.890
```

```
---
```

```
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
Step: vasc.hell ~ Ca + conduct
```

	Df	AIC	F	Pr(>F)	
+ Si	1	-48.180	2.2425	0.005	**
+ NH3	1	-47.931	1.9997	0.005	**
+ N03	1	-47.763	1.8367	0.005	**
+ Mg	1	-47.703	1.7788	0.005	**
+ Corg	1	-47.480	1.5629	0.020	*
+ Na	1	-47.442	1.5266	0.035	*
+ K	1	-47.257	1.3482	0.040	*
+ pH	1	-47.275	1.3658	0.050	*
+ S04	1	-47.125	1.2218	0.085	.
+ Fe	1	-47.304	1.3936	0.095	.
+ Cl	1	-46.916	1.0210	0.420	
+ P04	1	-46.709	0.8229	0.810	

```
---
```

```
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
Step: vasc.hell ~ Ca + conduct + Si
```

	Df	AIC	F	Pr(>F)	
+ NH3	1	-48.308	2.0060	0.005	**
+ N03	1	-48.234	1.9350	0.005	**
+ Mg	1	-47.972	1.6855	0.020	*
+ Corg	1	-47.807	1.5280	0.025	*
+ S04	1	-47.614	1.3446	0.055	.
+ pH	1	-47.622	1.3529	0.075	.
+ Na	1	-47.577	1.3104	0.095	.
+ Fe	1	-47.521	1.2568	0.105	
+ K	1	-47.509	1.2459	0.130	
+ Cl	1	-47.229	0.9815	0.470	
+ P04	1	-47.058	0.8199	0.805	

```
---
```

```
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
Step: vasc.hell ~ Ca + conduct + Si + NH3
```

	Df	AIC	F	Pr(>F)	
+ N03	1	-48.236	1.7875	0.005	**
+ Mg	1	-48.138	1.6951	0.005	**
+ S04	1	-47.824	1.4012	0.035	*
+ pH	1	-47.822	1.3998	0.045	*
+ Corg	1	-47.775	1.3558	0.045	*
+ Fe	1	-47.714	1.2986	0.125	
+ K	1	-47.547	1.1431	0.235	
+ Na	1	-47.459	1.0613	0.370	

```
+ Cl      1 -47.298 0.9112  0.665
+ P04     1 -47.195 0.8163  0.805
```

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: vasc.hell ~ Ca + conduct + Si + NH3 + N03

	Df	AIC	F	Pr(>F)	
+ Mg	1	-48.032	1.6369	0.010	**
+ pH	1	-47.858	1.4764	0.040	*
+ Corg	1	-47.713	1.3430	0.040	*
+ S04	1	-47.588	1.2288	0.135	
+ Fe	1	-47.530	1.1750	0.170	
+ K	1	-47.523	1.1693	0.210	
+ Na	1	-47.347	1.0080	0.480	
+ Cl	1	-47.233	0.9034	0.600	
+ P04	1	-47.164	0.8408	0.785	

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: vasc.hell ~ Ca + conduct + Si + NH3 + N03 + Mg

	Df	AIC	F	Pr(>F)	
+ pH	1	-47.709	1.5035	0.040	*
+ S04	1	-47.424	1.2453	0.095	.
+ Corg	1	-47.462	1.2795	0.100	.
+ Fe	1	-47.378	1.2040	0.115	
+ K	1	-47.401	1.2247	0.135	
+ Na	1	-47.110	0.9623	0.580	
+ Cl	1	-47.044	0.9036	0.650	
+ P04	1	-46.979	0.8450	0.775	

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Step: vasc.hell ~ Ca + conduct + Si + NH3 + N03 + Mg + pH

	Df	AIC	F	Pr(>F)	
+ Corg	1	-47.130	1.2508	0.140	
+ Fe	1	-47.054	1.1839	0.150	
+ K	1	-47.048	1.1785	0.175	
+ S04	1	-47.033	1.1650	0.185	
+ Na	1	-46.823	0.9783	0.595	
+ P04	1	-46.697	0.8676	0.715	
+ Cl	1	-46.694	0.8645	0.735	

Results are stored in sel.os object:

```
sel.os
```

```
Call: rda(formula = vasc.hell ~ Ca + conduct + Si + NH3 + N03 + Mg + pH,
```

```
data = chem1)
```

```
              Inertia Proportion Rank
Total          0.5674      1.0000
Constrained    0.1591      0.2804    7
Unconstrained  0.4083      0.7196   62
Inertia is variance
```

```
Eigenvalues for constrained axes:
```

```
  RDA1  RDA2  RDA3  RDA4  RDA5  RDA6  RDA7
0.09590 0.01904 0.01205 0.01027 0.00871 0.00718 0.00595
```

```
Eigenvalues for unconstrained axes:
```

```
  PC1  PC2  PC3  PC4  PC5  PC6  PC7  PC8
0.03601 0.03279 0.02383 0.01908 0.01687 0.01593 0.01504 0.01358
(Shown only 8 of all 62 unconstrained eigenvalues)
```

Selected variables are Ca, conduct, Si, NH3, NO3, Mg and pH.

From:

<https://www.davidzeleny.net/anadat-r/> - **Analysis of community ecology data in R**

Permanent link:

https://www.davidzeleny.net/anadat-r/doku.php/en:forward_sel_examples?rev=1554472328

Last update: **2019/04/05 21:52**